Timney Daniel Horner Trigger



The World's Finest Triggers®

TRIGGER INSTALLATION INSTRUCTIONS

Thank you for purchasing this Timney Trigger. It has been designed and manufactured to provide you with a lifetime of dependable service. Each trigger is hand tested and calibrated on a rifle action before leaving our factory. Please read these instructions **fully** before you begin installing the trigger, you'll be glad you did.

Installation Instructions

- 1. Before beginning work on any firearm, remove the ammunition source and double check to ensure the chamber is empty.
- To install the Timney Daniel Horner trigger the following tools are required:
 -Large flathead or Allen key, depending on your configuration, to remove the pistol grip.
 -5/64 Allen-key
- 3. To separate the upper and lower receiver, press out the two takedown pins (See image 1)
- 4. Remove pistol grip. From the bottom there should be a large screw visible inside the pistol grip, which should be removed using either an allen key or large flathead screwdriver. Ensure to retain both the safety spring and plunger from the top end of the pistol grip NOTE: remember the order and orientation in which the spring and plunger came out (See image 2)
- 5. Remove the pins which mount the original trigger (See image 3)
- 6. Remove the safety lever and fire control (See image 4)
- 7. Remove original trigger
- 8. Insert your new Timney Daniel Horner trigger in the lower receiver and insert the pins.
- 9. Reinstall the fire control selector, safety plunger and pistol grip and tighten the 2 mounting screws using the 5/64 allen key (See image7)
- 10. To set the pull weight use the 5/64 allen key to adjust the set screw visible on top of the trigger. (See image 8) Turn clockwise to increase the pull weight, counter clockwise to reduce the pull weight.
- 11. Reinstall the upper receiver on the lower receiver and press in the two takedown pins (See image 9)
- 12. Perform a function check and enjoy your new Timney Trigger.



NOTE: If you have trouble, contact Timney or check out the troubleshooting steps on the Timney web site. Timney will also install your trigger for \$ 40.00 plus \$ 35.00 shipping and handling.

TIMNEY TRIGGER GUARANTEE

Material and workmanship: This Timney trigger has been carefully inspected, tested and adjusted to give a lifetime of dependable service. Every possible care has been exercised in its design and construction. If any defect in workmanship or material should develop under conditions of normal use and service, any necessary repairs, including parts and labor will be made at NO CHARGE to the purchaser providing that our inspection reveals parts were not damaged through accident, alteration, misuse, abuse or other causes beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume for us any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific authorization, voids the guarantee.