

Timney MPX Triggers

MPX INSTALLATION INSTRUCTIONS

Thank you for purchasing this Timney Trigger for your MPX, your trigger is compatible with all calibers. It has been designed and manufactured to provide you with a lifetime of dependable service. Each trigger is hand tested and calibrated on a rifle action before leaving our factory. Please read these instructions **fully** before you begin installing the trigger, you'll be glad you did.

You'll need a 1/8 punch, six inch flat-tip screw driver or hex wrench for pistol grip removal and the included 5/64 Allen wrench for installation.

Installation Instructions

- 1. After unloading the rifle place the safety to fire and pull the trigger in a safe direction.
- 2. Separate the upper and lower receivers.
- 3. Insert a screwdriver or hex wrench inside the grip and remove the grip screw.
- 4. Maintain pressure on the grip as you remove the screw.
- 5. Remove the safety lever.
- 6. Slowly remove the grip being careful not to lose the safety spring and plunger.
- 7. Push out the hammer and trigger pins and remove all trigger parts.
- 8. Slide the trigger bridge over the rear end of the trigger. Make sure to point the beveled edges away from the trigger, towards the safety selector.
- 9. Place the base plate under the trigger, this will prevent the setscrews galling your lower receiver.
- 10. Insert the the Timney Trigger into the trigger well.
- 11. Install the safety (Did you know Timney makes a short throw ambidextrous safety?)
- 12. Reinstall the hammer and trigger pins.
- 13. Using the included 5/64 Allen wrench tighten down the two lock screws in the trigger housing indicated by the threaded holes on either side of the housing.
- 14. Notice there are only two screws to tighten down and they are already in the housing. A Nylock dowel will hold the trigger screws in place.
- 15. Function check trigger in both the safe and fire positions.

Technicalsupport@timneyusa.com Phone: 623-223-1111 • Fax: 623-223-1112 www.timneytriggers.com 2020 W. Quail Avenue • Phoenix, AZ 85027







Reminder:

This trigger does not use the second set of lock screws.

NOTE: If you have trouble, contact Timney or check out the troubleshooting steps on the Timney website www.timneytriggers.com. Timney will also install your trigger for \$40.00 plus \$35.00 shipping and handling. Be sure to send beef jerky along with all installs.

TIMNEY TRIGGER GUARANTEE

Material and workmanship: This Timney trigger has been carefully inspected, tested and adjusted to give a lifetime of dependable service. Every possible care has been exercised in its design and construction. If any defect in workmanship or material should develop under conditions of normal use and service, any necessary repairs, including parts and labor will be made at NO CHARGE to the purchaser providing that our inspection reveals the trigger was not damaged through accident, alteration, misuse, abuse or other causes beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume for us any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific authorization voids the guarantee.

Be sure to check out the live chat feature on the Timney website and connect directly with a Trigger Jedi to answer all questions regarding installation or function of your Timney Trigger.

P.S.: Did you know you can purchase triggers directly from Timney at www.timneytriggers.com

Timney Triggers LLC • 2020 W. Quail Ave. Phoenix, AZ 85027 • www.timneytriggers.com Phone: 623-223-1111 • Fax: 623-223-1112 • service@timneyusa.com