

The World's Finest Triggers®

## TRIGGER INSTALLATION INSTRUCTIONS

Thank you for purchasing this Timney Trigger. It has been designed and manufactured to provide you with a lifetime of dependable service. Each trigger is hand tested and calibrated on a rifle action before leaving our factory. Please read these instructions **fully** before you begin installing the trigger, you'll be glad you did.

## Installation Instructions

- 1. Before beginning work on any firearm, remove the ammunition source and double check to ensure the chamber is empty.
- 2. To install the Timney Weatherby Mk5 trigger the following tools are required:
  - -Large flathead screwdriver.
  - -1/8 Allen-key
  - -5/32 Allen-key
  - -5/64 Allen-key
- 3. To remove the bolt, pull the trigger while pulling the bolt rearwards out of the receiver.
- 4. Use a large flathead screwdriver to remove the action screws in the bottom metal to lift the action out of the stock
- 5. Remove the socket head screw visible on the bottom of the trigger
- 6. Remove the countersunk Allen-screw visible in the tang
- 7. Remove original trigger and insert you new Timney trigger with the 2 original Allen-screws,
- 8. Insert the action back in the stock and with the magazine and bottom metal in place torque the 2 action screws to factory recommended spec.
- 9. Insert the bolt while keeping the trigger to the rear, perform a function check and enjoy your new Timney trigger!
- 10. The trigger's pull weight is adjustable from 1.5lbs-4lbs, to adjust the pull weight adjust the setscrew visible from the bottom with a 5/64 Allen-key. Turn clockwise to increase pull weight and counterclockwise to decrease the pull weight.



**NOTE:** If you have trouble, contact Timney or check out the troubleshooting steps on the Timney web site. Timney will also install your trigger for \$40.00 plus\$ 35.00 shipping and handling.

## TIMNEY TRIGGER GUARANTEE

Material and workmanship: This Timney trigger has been carefully inspected, tested and adjusted to give a lifetime of dependable service. Every possible care has been exercised in its design and construction. If any defect in workmanship or material should develop under conditions of normal use and service, any necessary repairs, including parts and labor will be made at NO CHARGE to the purchaser providing that our inspection reveals parts were not damaged through accident, alteration, misuse, abuse or other causes beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume for us any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific authorization, voids the guarantee.